

# ICI HH500-15 L-EFT

Pulse Magnetic Field Source

**LANGER**  
EMV-Technik




## Short description

The ICI HH500-15 L-EFT pulse magnetic field source couples fast transient pulses into a test IC (open die). This allows for electromagnetic fault injection (EMFI) attacks or testing the immunity of individual areas of the IC.


## Technical parameters

<b>Probe head dimensions</b>	Ø 500 µm
<b>magnetic flux density (typ.)</b>	50 mT
<b>Pulse parameter</b>	
Rise time	< 2 ns
Repetition frequency	0.1 Hz - 20 kHz
Polarity (set by software)	+ / - / alternating
<b>Measuring output</b>	50 Ω
<b>Trigger-pulse delay (Bypass Mode - Delay Line)</b>	
min. Trigger-pulse delay (typ.)	70 ns
max. Trigger-pulse delay (typ.)	420 ns
max. Jitter (typ.)	± 1 ns
<b>Supply voltage</b>	BPS 202
<b>Weight</b>	70 g
<b>Sizes (L x W x H)</b>	(26 x 43 x 53) mm

### Pulse shape



### Transverse scan



# ICI HH500-15 L-EFT

Pulse Magnetic Field Source

Application of ICI HH500-15 L-EFT pulse magnetic field source

